



SAFETY DATA SHEET

Holts GREY Primer

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	Holts GREY Primer
PRODUCT NO.	L106C
APPLICATION	Paint.
SUPPLIER	Holt Lloyd International Ltd Barton Dock Road Stretford Manchester M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854 A Holts Car Care Product www.holtsauto.com
CONTACT PERSON	Regulatory Affairs
EMERGENCY TELEPHONE	FR - INRS Tél :+33 (0)1.45.42.59.59 24hrs B - Antigifcentrum Tél: +32.70.245.245 24hrs NL - Rijksinstituut voor Volksgezondheid en Milieuhygiëne: tel. +31 (0)30 274 91 11 24hrs D - +49 (0)89 19240 UK - 00 44 (0) 161 491 7391 office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358 9167

2 HAZARDS IDENTIFICATION

Extremely flammable Irritating to eyes. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

CLASSIFICATION (1999/45) Xi;R36. F+;R12. N;R51/53. R66, R67.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
DIMETHYL ETHER	204-065-8	115-10-6	30-60%	F+;R12
ACETONE	200-662-2	67-64-1	10-30%	F;R11 Xi;R36 R66 R67
BUTYL ACETATE -norm	204-658-1	123-86-4	5-10%	R10 R66 R67
ISOBUTANE	200-857-2	75-28-5	5-10%	F+;R12
BUTANE	203-448-7	106-97-8	5-10%	F+;R12
2-METHOXY-1-METHYLETHYL ACETATE	203-603-9	108-65-6	1-5%	R10 Xi;R36
BUTANONE	201-159-0	78-93-3	1-5%	F;R11 Xi;R36 R66 R67
BUTANOL-norm	200-751-6	71-36-3	1-5%	R10 Xn;R22 Xi;R37/38,R41 R67
TRIZINC BIS(ORTHOPHOSPHATE)	231-944-3	7779-90-0	1-5%	N;R50/53

The Full Text for all R-Phrases is Displayed in Section 16

Holts GREY Primer**4 FIRST-AID MEASURES****INHALATION**

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

Rinse mouth thoroughly. Provide rest, warmth and fresh air. DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS!

SKIN CONTACT

Remove affected person from source of contamination. Get medical attention if any discomfort continues.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES**EXTINGUISHING MEDIA**

Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

6 ACCIDENTAL RELEASE MEASURES**SPILL CLEAN UP METHODS**

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate.

7 HANDLING AND STORAGE**USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
2-METHOXY-1-METHYLETHYL ACETATE	WEL	50 ppm(Sk)	274 mg/m3(Sk)	100 ppm(Sk)	548 mg/m3(Sk)	
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3	
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
BUTANOL-norm	WEL			50 ppm(Sk)	154 mg/m3(Sk)	
BUTANONE	WEL	200 ppm(Sk)	600 mg/m3(Sk)	300 ppm(Sk)	899 mg/m3(Sk)	
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3	
DIMETHYL ETHER	WEL	400 ppm	766 mg/m3	500 ppm	958 mg/m3	
ISOBUTANE	OES	800 ppm		800 ppm		

WEL = Workplace Exposure Limit.

Holts GREY Primer**PROTECTIVE EQUIPMENT****RESPIRATORY EQUIPMENT**

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves. EN374 Rubber gloves are recommended.

EYE PROTECTION

Wear approved safety goggles.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. **DO NOT SMOKE IN WORK AREA!**

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol.
COLOUR	Grey.
RELATIVE DENSITY	~0.7945
VOLATILE BY VOL. (%)	89.2%
AUTO IGNITION	235C
TEMPERATURE (°C)	
FLAMMABILITY LIMIT - LOWER(%)	2.6%
FLAMMABILITY LIMIT - UPPER(%)	18.6%
VOLATILE ORGANIC COMPOUND (VOC)	708.7 g/litre

10 STABILITY AND REACTIVITY**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire or high temperatures create: Acrid smoke/fumes of: Carbon dioxide (CO₂). Carbon monoxide (CO).

11 TOXICOLOGICAL INFORMATION**INHALATION**

Vapours may cause headache, fatigue, dizziness and nausea. When working extensively on big surfaces in small and badly ventilated rooms, vapours may develop in concentrations which may cause headache and irritation of the eyes and the respiratory system.

INGESTION

No harmful effects expected in amounts likely to be ingested by accident.

SKIN CONTACT

Prolonged and frequent contact may cause redness and irritation.

EYE CONTACT

Irritating to eyes. Repeated exposure may cause chronic eye irritation.

Holts GREY Primer**ROUTE OF ENTRY**

Inhalation. Skin and/or eye contact.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

Not regarded as dangerous for the environment. The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

13 DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements. Empty containers must not be burned because of explosion hazard.

14 TRANSPORT INFORMATION

PROPER SHIPPING NAME	AEROSOLS (TRIZINC BIS(ORTHOPHOSPHATE))
UN NO. ROAD	1950
ADR CLASS NO.	2.1
ADR CLASS	Class 2: Gases
TUNNEL RESTRICTION CODE	(D)
ADR LABEL NO.	2.1
UN NO. SEA	1950
IMDG CLASS	2.1
EMS	F-D, S-U
UN NO. AIR	1950
AIR CLASS	2.1

15 REGULATORY INFORMATION**LABELLING**

Irritant



Extremely flammable



Dangerous for the environment

RISK PHRASES

R12	Extremely flammable.
R36	Irritating to eyes.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.

Holts GREY Primer

SAFETY PHRASES	R67	Vapours may cause drowsiness and dizziness.
	A1	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
	A2	Do not spray on a naked flame or any incandescent material.
	S2	Keep out of the reach of children.
	S16	Keep away from sources of ignition - No smoking.
	S23	Do not breathe vapour/spray.
	S25	Avoid contact with eyes.
	S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	S37	Wear suitable gloves.
	S51	Use only in well-ventilated areas.
	S29/56	Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. VOC Directive - 2004/42/EC Aerosol Dispensers Directive 2008/47/EC (2008/47/EC)

NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

16 OTHER INFORMATION

REVISION DATE	16/08/2011
---------------	------------

REV. NO./REPL. SDS GENERATED	11
------------------------------	----

SDS NO.	14252
---------	-------

DATE	6/08/2011
------	-----------

RISK PHRASES IN FULL

R12	Extremely flammable.
R10	Flammable.
R22	Harmful if swallowed.
R11	Highly flammable
R36	Irritating to eyes.
R37/38	Irritating to respiratory system and skin.
R66	Repeated exposure may cause skin dryness or cracking.
R41	Risk of serious damage to eyes.
R67	Vapours may cause drowsiness and dizziness.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.