

## SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH)

## **QUARTZ 9000 NFC 5W-30**

**SDS no.** 090271

2

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

**Product name** 

: QUARTZ 9000 NFC 5W-30

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses			
Motor oil			

### 1.3 Details of the supplier of the safety data sheet

TOTAL LUBRIFIANTS 562 Avenue du Parc de L'ile 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71

rm.msds-lubs@total.com

TOTAL UK LIMITED 183 Eversholt St, Kings Cross London, NW1 1BU UNITED KINGDOM Tel: +44 (0)20 7339 8000 Fax: +44 (0)20 7339 8033 rm.gb-msds@total.co.uk

Contact

2/22/2021

H.S.E

1.4 Emergency telephone number			
National advisory body/Poison Centre			
Telephone number	: National Poisons Information Service (NPIS): 111		
<u>Supplier</u>			
Telephone number	: Emergency telephone: +44 1235 239670		

### **SECTION 2: Hazards identification**

2.1 Classification of t	he substance or mixture	
Product definition	: Mixture	
Classification accor Not classified.	ding to Regulation (EC) I	No. 1272/2008 [CLP/GHS]
The product is not cla	ssified as hazardous acco	rding to Regulation (EC) 1272/2008 as amended.
Ingredients of unkn toxicity	2.7 percent of toxicity	the mixture consists of component(s) of unknown acute oral toxicity the mixture consists of component(s) of unknown acute dermal the mixture consists of component(s) of unknown acute inhalation
Date of revision :	Version : 1	United Kingdom (UK) ENGLISH 1/15



See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	:	Not applicable.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	Contains C14-16-18 Alkyl phenol. May produce an allergic reaction. Safety data sheet available on request.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.

### 2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do** : Prolonged or repeated contact may dry skin and cause irritation. **not result in classification** 

### **SECTION 3: Composition/information on ingredients**

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Lubricating oils (petroleum),	REACH #:	≥50 - ≤75	Asp. Tox. 1, H304	[1]
C20-50, hydrotreated neutral oil-	01-2119474889-13			
based	EC: 276-738-4			
	CAS: 72623-87-1			
C14-16-18 Alkyl phenol	REACH #:	≤3	Skin Sens. 1B, H317	[1]
	01-2119498288-19		STOT RE 2, H373	
	EC: 931-468-2			
bis(nonylphenyl)amine	REACH #:	≤3	Aquatic Chronic 4,	[1]
	01-2119488911-28		H413	
	EC: 253-249-4			
	CAS: 36878-20-3			
Distillates (petroleum),	REACH #:	≤3	Asp. Tox. 1, H304	[1]
hydrotreated heavy paraffinic	01-2119484627-25			
	EC: 265-157-1			
	CAS: 64742-54-7			
			See Section 16 for	
			the full text of the H	
			statements declared	
			above.	

ation : Mineral oil of petroleum origin Product containing mineral oil with less than 3% DMSO extract as measured by IP 346



SDS no. 090271

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

### 4.1 Description of first aid measures

Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.</li> </ul>		
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.		
Skin contact	: Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.		
Ingestion	: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.		

### 4.2 Most important symptoms and effects, both acute and delayed

#### **Over-exposure signs/symptoms**

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.



SDS no. 090271

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media Suitable extinguishing media	:	Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.		
Unsuitable extinguishing media	:	Do not use water jet.		
5.2 Special hazards arising f	rom	the substance or mixture		
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst.		
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides		
5.3 Advice for firefighters	5.3 Advice for firefighters			
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.		
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.		

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.		
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
6.3 Methods and material for containment and cleaning up			
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.		
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.		



SDS no. 090271

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.
See Section 13 for additional waste treatment information.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Protective measures Advice on general occupational hygiene	<ul> <li>Put on appropriate personal protective equipment (see Section 8).</li> <li>Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.</li> </ul>
--	--

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational exposure limits**

No exposure limit value known.

## Reportable hazardous constituent(s) contained in UVCB- and/or multi-constituent substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

No exposure limit value known.

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Advisory OEL	:	Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH (TLV) TWA 5 mg/m3 (highly refined)

### **DNELs/DMELs**



SDS no. : 090271

	_	_			
Product/substance	Туре	Exposure	Value	Population	Effects
Lubricating oils (petroleum), C20-50,	DNEL	Long term	5.4 mg/m <sup>3</sup>	Workers	Local
hydrotreated neutral oil-based		Inhalation			
	DNEL	Long term	1.2 mg/m³	General	Local
		Inhalation		population	
C14-16-18 Alkyl phenol	DNEL	Long term Inhalation	1.17 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	0.3 mg/kg bw/day	Workers	Systemic
bis(nonylphenyl)amine	DNEL	Long term Oral	0.25 mg/	General	Systemic
bis(nonyiphonyi)amino	DIVLL	Long term ordi	kg bw/day	population	Cysternio
	DNEL	Long term Dermal	2.5 mg/kg	General	Systemic
		5	bw/day	population	,
	DNEL	Long term Dermal	5 mg/kg	Workers	Systemic
			bw/day	14/	
	DNEL	Long term Dermal	0.62 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term	4.37 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation	-		
Distillates (petroleum), hydrotreated	DNEL	Long term	5.58 mg/m <sup>3</sup>	Workers	Local
heavy paraffinic		Inhalation			
	DNEL	Long term	1.19 mg/m <sup>3</sup>		Local
		Inhalation	740	population	
	DNEL	Long term Oral	740 µg/kg	General	Systemic
	DNEL	Long term Dermal	970 µg/kg	population Workers	Systemic
	DNEL	Long term	2.73 mg/m <sup>3</sup>		Systemic
		Inhalation	2.75 mg/m	VVUINCIS	Gysternic

### PNECs

Product/ingredient name	Compartment Detail	Name	Method Detail
C14-16-18 Alkyl phenol	Fresh water	0.1 mg/l	-
	Marine water	0.01 mg/l	-
		4266.16 mg/kg dwt	-
	Marine water sediment	426.62 mg/kg dwt	
	Soil Sewage Treatment Plant	852.58 mg/kg dwt 100 mg/l	-
bis(nonylphenyl)amine	Fresh water	0.1 mg/l	-
	Marine water Fresh water sediment	0.01 mg/l 132000 mg/kg dwt	-
	Marine water sediment	13200 mg/kg dwt 263000 mg/kg dwt	-
	Sewage Treatment Plant	1 mg/l	-

#### 8.2 Exposure controls

Appropriate engineering<br/>controls: Good general ventilation should be sufficient to control worker exposure to airborne<br/>contaminants.

### Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.



SDS no.	090271	
•		

Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Hydrocarbon-proof gloves nitrile rubber Fluorinated rubber Please observe the instructions regarding permeability and breakthrough time
	which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency
Body protection	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Respirator with combination filter for vapour/particulate Type A/P1 Warning ! filters have a limited use duration The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses None under normal use conditions
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid. [Clear]
Colour	: Not available.
Odour	: Characteristic.
Odour threshold	: Not available.
рН	Not applicable.
Melting point/freezing point	: Not available.
Initial boiling point and	: Not available.
boiling range	
Flash point	: Open cup: 230°C [Cleveland Open Cup (COC)]
Evaporation rate	: Not available.



SDS no. 090271

Flammability (solid, gas)	: Not available.
Upper/lower flammability or explosive limits	: Not available.
Vapour pressure	: Not available.
Vapour density	: Not available.
Relative density	: 0.846 to 0.856
Solubility(ies)	: Insoluble in the following materials: cold water and hot water.
Partition coefficient: n-octanol/ water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C): 0.54 cm <sup>2</sup> /s [ASTM D 445 ]
Explosive properties	: Not available.
Oxidising properties	: Not applicable
9 2 Other information	

9.2 Other information		
Solubility in water	:	Insoluble

## **SECTION 10: Stability and reactivity**

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: Strong oxidising agents
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

### Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
C14-16-18 Alkyl phenol	LD50 Dermal	Rat	2000 mg/kg	-	-
2.1	LD50 Oral	Rat	2000 mg/kg	-	-
bis(nonylphenyl)amine	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	-
	LD50 Dermal	Rat	>2000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401



SDS no. 090271 :

hydrotreated heavy paraffinic	and mists LD50 Dermal LD50 Oral	Rabbit Rat	>5000 mg/kg >5000 mg/kg		OECD 402 OECD 420
Distillates (petroleum),	LC50 Inhalation Dusts	Rat	5.1 mg/l	4 hours	OECD 403

### Acute toxicity estimates

Product/substance	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	N/A	N/A	N/A	N/A	5.1
bis(nonylphenyl)amine	N/A	N/A	N/A	N/A	5.1
Distillates (petroleum), hydrotreated heavy paraffinic	N/A	N/A	N/A	N/A	5.1

Irritation/Corrosion

Conclusion/Summary	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
<u>Sensitisation</u>	
Conclusion/Summary	:
Conclusion/Summary	: The supplier of one or more of the components contained within this formulation has indicated that he has data on the components and/or similar mixtures, which confirms that at the concentration used, classification is not required
<u>Mutagenicity</u>	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b>	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
Reproductive toxicity	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
<u>Teratogenicity</u>	
Conclusion/Summary	: Based on available data, the classification criteria are not met.
Specific target organ toxici	<u>ty (single exposure)</u>

Not available.

### Specific target organ toxicity (repeated exposure)

Product/substance	Category	Route of exposure	Target organs
C14-16-18 Alkyl phenol	Category 2	Not determined	Not determined

### Aspiration hazard

Product/substance	Result
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1

#### Information on likely routes : Not available. of exposure

### Potential acute health effects



SDS no. 090271

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the phy	vsical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.
	ts as well as chronic effects from short and long-term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

### Other information

: Not available.

## **SECTION 12: Ecological information**

12.1 Toxicity



SDS no. : 090271

<b>F</b>	1		i	
Product/substance	Result	Species	Exposure	Test
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Acute EC50 >100 mg/l	Algae - Pseudokirchnerella subcapitata	48 hours	OECD 201
	Acute EC50 >10000 mg/l Acute LC50 >10000 mg/l	Daphnia - Daphnia magna Daphnia - Gammarus	48 hours 24 hours	OECD 202 OECD 202
	Acute LC50 >10000 mg/l	pulex Daphnia - Gammarus pulex	48 hours	OECD 202
	Acute LC50 >10000 mg/l	Daphnia - Gammarus pulex	72 hours	OECD 202
	Acute LC50 >10000 mg/l	Daphnia - Gammarus pulex	96 hours	OECD 202
	Acute NOEL 101 mg/l Acute NOEL >100 mg/l	Algae Fish - Pimephales promelas	72 hours 96 hours	OECD 201 OECD 203
	Chronic NOEL 10 mg/l Chronic NOEL >1000 mg/l	Daphnia - Daphnia magna Fish - Oncorhynchus mykiss	21 days 21 days	OECD 211 -
C14-16-18 Alkyl phenol bis(nonylphenyl)amine	Acute EC50 >100 mg/l Acute EC50 600 mg/l	Daphnia - Daphnia magna Algae - Selenastrum capricornutum	48 hours 72 hours	OECD 202 -
	Acute EC50 >100 mg/l Acute EC50 >1000 mg/l	Daphnia - Daphnia magna Micro-organism	48 hours 0.1 days	OECD 202 -
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Algae - Pseudokirchnerella	48 hours	OECD 201
	Acute EC50 >10000 mg/l Chronic NOEL 10 mg/l Chronic NOEL >1000 mg/l	subcapitata Daphnia - Daphnia magna Daphnia - Daphnia magna Fish - Oncorhynchus	48 hours 21 days 21 days	OECD 202 - -
		mykiss		

### 12.2 Persistence and degradability

Conclusion/Summary : Not available.			
Product/substance	Aquatic half-life	Photolysis	Biodegradability
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	-	-	Not readily
bis(nonylphenyl)amine	-	-	Not readily

### 12.3 Bioaccumulative potential

Product/substance	LogK <sub>ow</sub>	BCF	Potential
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based bis(nonylphenyl)amine Distillates (petroleum), hydrotreated heavy paraffinic	7.7 >4	- 1584.89 -	high high high

### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.



SDS no. 090271

Mobility in soil

: Given its physical and chemical characteristics, the product generally shows low soil mobility. The product is insoluble and floats on water. Loss by evaporation is limited

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects	No known significant effects	or critical hazards.
	NO KHOWH SIGHINGALL ELECIS	

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used The following Waste Codes are only suggestions: 13 02 05*
<u>Packaging</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.



SDS no.	090271
•	

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk	: Not available.
according to Annex II of	
Marpol and the IBC Code	

### **SECTION 15: Regulatory information**

U Regulation (EC) No. 190	nces subject to authorisation
Annex XIV	
None of the components a	re listed
Substances of very high	
None of the components a	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	
Other EU regulations	
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed
Ozone depleting substanc	<u>es (1005/2009/EU)</u>
Not listed.	
Prior Informed Consent (P Not listed.	IC) (649/2012/EU)
Seveso Directive This product is not controlled Iational regulations	d under the Seveso Directive.

### **International regulations**

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)



SDS no. 090271

	· · · ·			
Not listed.				
Stockholm Convention on Persistent Organic Pollutants				
Not listed.				
Rotterdam Convention of	on Prior Informed Consent (PIC)			
Not listed.				
UNECE Aarbus Brotoss	on POPs and Heavy Metals			
Not listed.	OII FORS and neavy metals			
Inventory list				
Australia	: All components are listed or exempted.			
Canada	: All components are listed or exempted.			
China	: All components are listed or exempted.			
Europe	: All components are listed or exempted.			
Japan	: Japan inventory (ENCS): All components are listed or exempted. Japan inventory (ISHL): Not determined.			
New Zealand	: All components are listed or exempted.			
Philippines	: All components are listed or exempted.			
Republic of Korea	: All components are listed or exempted.			
Taiwan	: All components are listed or exempted.			
Thailand	: Not determined.			
Turkey	: Not determined.			
United States	: All components are listed or exempted.			
Viet Nam	: Not determined.			
15.2 Chemical safety assessment	: This product contains substances for which Chemical Safety Assessments are still required.			

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Value	: ATE = Acute Toxicity Estimate
	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

### Full text of abbreviated H statements



SDS no. 090271

H304 H317 H373	May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure.
H413	May cause long lasting harmful effects to aquatic life.
Full text of classifications [CLP/GHS]	
Aquatic Chronic 4, H413 Asp. Tox. 1, H304 Skin Sens. 1B, H317 STOT RE 2, H373	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4 ASPIRATION HAZARD - Category 1 SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

Date of revision	:	2/22/2021
Date of previous revision	:	No previous validation
Version	:	1

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.